

PS MANUAL

SMARTWASHER®

1.0 <u>Model</u> DSW-123M

- 2.0 <u>Description</u>
 - 1 x Mobile SmartWasher® 123M



Durst Industries Australia Pty. Ltd. durst.com.au Phone: +61 2 9660 1755

Unit 1, 11 Packard Avenue Castle Hill NSW 2154 Australia







3.0 <u>Features</u>

- ON/OFF control, side mounted
- Flow timer with 10 and 30 minute increments
- Flow through parts brush
- User regulated independent flow control from brush or nozzle
- Thermostat maintains fluid at 42° C (adjustable to 46° C)
- Does not damage Neoprene or Rubber gaskets and seals
- Indicators: Low Fluid level indicator (Red) Standby/ ready indicator (Green) Power Indicator (Green)
 - Complies with Australian WHS Regulations
- Complies with Australian WHS Regulations
 Patented as a non-hazardous bio remediating parts cleaning system
- Uses warm aqueous degreasing solution called " Ozzy Juice®"
- Reduces the release of VOC's and eliminates hazardous waste.
- Helps save our environment whilst protecting the health and wellbeing of your employees.

SmartWasher® Certificates and Approvals

AQMD Certified DSW-SW3 Truck Grade OzzyJuice®. DSW-SW6-8 Weapons Aviation Grade OzzyJuice®.



Authorization to Mark



Declaration of Conformity



Test Certificate in Compliance with the Device Safety Act

Test Certificate in Compliance with the Device Safety Act National Sanitation Foundation. DSW-SW3, DSW-SW6-8 OzzyJuice®



Product Safety Certificate

4.0 <u>Physical and Dimensional Properties</u>

- Each unit weighs approximately 33.0Kg Empty
- Approximate Shipping Weight: 53.0Kg
- Material: Blow moulded High Density polyethylene



PS MANUAL

Overall Dimensions

- Width 685 mm
- Length 1090 mm
- Height 1050 mm

Inside Sink Dimensions

- Width 590 mm
- Length 650 mm
- Height 204 mm

Shipping Dimensions

- Width 712 mm
- Length 1230 mm
- Height 1130 mm

5.0 <u>Performance</u>

- Pump Capacity: 93.75 Kw; 170 GPH at 1 foot; sump intake see DSW-PU20
- Electrical: 240 Volt, 50 Hz
- Heater: 1000 Watt industrial Heater -see DSW-1285
- Capacity: Holds 250Kg Load
- Filtration: Microbe impregnated 50 micron filters changeable and disposable without special tools or equipment. see **DSW-FL4-3PK** and **MSDS FL4**
- Cleaning Solution: OzzyJuice® see DSW-SW3 and MSDS SW3 Aqueous based surfactant cleaner. NO Flashpoint PH Neutral biodegradable Non-Toxic, no caustic, non flammable, non hazardous NO VOC's, Phosphates, formaldehyde, bio solvents or solvents.
 Microbe Treatment: Ozzy BoosterTM - see DSW-1070 and MSDS 1070
- Microbe Treatment. 022y Booster ¹³⁴ see DSW-1070 and WS. Environmental- shock resistant; Preserved for minimum 18 months shelf life. Natural occurring, non- pathogenic microbes

6.0 <u>Uses</u>

• Suitable for Car/Truck dealer workshops, Panel Beaters, Bus repairers, Mining Companies, Aviation, Defence, Councils, TAFE,

7.0 <u>Documentation</u>

- Bar Code Number: **9346080000013**
- Product Specification Manual PS 96
- Work Instruction Manual WI 96
- Product Costing Manual PC 96

