



PS MANUAL

SMARTWASHER

1.0 Model **DSW-125**

2.0 Description

1 x Mobile SmartWasher 125

IP 65 Rated



Durst Industries Pty Ltd

189 St Johns Road
Glebe NSW 2037

Website: www.durst.com.au
Phone: 02 9660 1755
Fax: 02 9692 0251

REV: NIL

Kevin Pitt

PS: 97

DATE: 08/08/13

AUTHORISED BY

PAGE: 1 of 3



3.0 Features

- ON/OFF control, side mounted
- Flow timer with 10 and 30 minute increments
- Flow through parts brush
- User regulated independent flow control from brush or nozzle
- Thermostat maintains fluid at 42° C (adjustable to 46° C)
- Does not damage Neoprene or Rubber gaskets and seals
- Warm cleaning solution
- Indicators: Low Fluid level indicator (**Red**)
Standby/ ready indicator (**Green**)
Power Indicator (**Green**)
- Complies with Australian WHS Regulations
- Patented as a non-hazardous bio remediating parts cleaning system
- Uses warm aqueous degreasing solution called " Ozzy Juice"
- Reduces the release of VOC's and eliminates hazardous waste.
- Helps save our environment whilst protecting the health and wellbeing of your employees.

SmartWasher Certificates and Approvals



AQMD Certified
DSW-SW3 Truck Grade OzzyJuice.
DSW-SW6-8 Weapons Aviation Grade OzzyJuice.



Authorization to Mark



Declaration of Conformity



Test Certificate in Compliance with the Device Safety Act



Test Certificate in Compliance with the Device Safety Act
National Sanitation Foundation. DSW-SW3, DSW-SW6-8 OzzyJuice



Product Safety Certificate

4.0 Physical and Dimensional Properties

- Approximate Shipping Weight: 53.0Kg
- Each unit weighs approximately 73.0Kg Empty
- Material: Blow moulded High Density polyethylene



Overall Dimensions

- Width 978 mm
- Length 737 mm
- Height 1004 mm

Inside Sink Dimensions

- Width 661 mm
- Length 420 mm
- Height 204 mm

Shipping Dimensions

- Width 991 mm
- Length 737 mm
- Height 1042 mm

5.0 Performance

- Pump Capacity: 93.75 Kw; 170 GPH at 1 foot; sump intake – see **DSW-PU20**
- Electrical: 240 Volt, 50 Hz
- Heater: 1000 Watt industrial Heater –see **DSW-1285**
- Capacity: Holds 250Kg Load
- Filtration: Microbe impregnated 50 micron filters changeable and disposable without special tools or equipment. – see **DSW-FL4-3PK** and **MSDS FL4**
- Cleaning Solution: OzzyJuice – see **DSW-SW3** and **MSDS SW3**
Aqueous based surfactant cleaner.
NO Flashpoint
PH Neutral biodegradable
Non-Toxic, no caustic, non flammable, non hazardous
NO VOC's, Phosphates, formaldehyde, bio solvents or solvents.
- Microbe Treatment: Ozzy Booster - see **DSW-1070** and **MSDS 1070**
Environmental- shock resistant;
Preserved for minimum 18 months shelf life.
Natural occurring, non- pathogenic microbes
- Mobile Trolley – see **DSW-1260**

6.0 Uses

- Suitable for Car/Truck dealer workshops, Panel Beaters, Bus repairers, Mining Companies, Aviation, Defence, Councils, TAFE,

7.0 Documentation

- Bar Code Number: **934608000044**
- Product Specification Manual - PS 97
- Work Instruction Manual - WI 97
- Product Costing Manual - PC 97