



PS MANUAL

## HEAVYWEIGHT SMARTWASHER

1.0 Model **DSW-137M**

2.0 Description

1 x Mobile HeavyWeight SmartWasher 137



Durst Industries Pty Ltd

189 St Johns Road  
Glebe NSW 2037

Website: [www.durst.com.au](http://www.durst.com.au)  
Phone: 02 9660 1755  
Fax: 02 9692 0251

REV: NIL

*Kevin Pitt*

PS: 256

DATE: 10/12/13

AUTHORISED BY

PAGE: 1 of 3



### 3.0 Features

- ON/OFF control, side mounted
- Flow timer with 10 increments
- Flow through parts brush
- User regulated independent flow control from brush or nozzle
- Thermostat maintains fluid at 42° C (adjustable to 46° C)
- Does not damage Neoprene or Rubber gaskets and seals
- Warm cleaning solution
- Indicators: Low Fluid level indicator ( **Red** )  
Standby/ ready indicator ( **Green** )  
Power Indicator ( **Green** )
- Complies with Australian WHS Regulations
- Patented as a non-hazardous bio remediating parts cleaning system
- Uses warm aqueous degreasing solution called " Ozzy Juice"
- Reduces the release of VOC's and eliminates hazardous waste.
- Helps save our environment whilst protecting the health and wellbeing of your employees.

#### SmartWasher Certificates and Approvals



AQMD Certified  
DSW-SW3 Truck Grade OzzyJuice.  
DSW-SW6-8 Weapons Aviation Grade OzzyJuice.



Authorization to Mark



Declaration of Conformity



Test Certificate in Compliance with the Device Safety Act



Test Certificate in Compliance with the Device Safety Act  
National Sanitation Foundation. DSW-SW3, DSW-SW6-8 OzzyJuice



Product Safety Certificate

### 4.0 Physical and Dimensional Properties

- Each unit weighs approximately **TBA**Kg Empty
- Approximate Shipping Weight: **TBA**Kg
- Material: Blow moulded High Density polyethylene



## PS MANUAL

### Overall Dimensions

- Width 889 mm
- Length 1219 mm
- Height 11430 mm

### Inside Sink Dimensions

- Width 838 mm
- Length 686 mm
- Height 203 mm

### Shipping Dimensions

- Width **TBA** mm
- Length **TBA** mm
- Height **TBA** mm

### 5.0 Performance

- Pump Capacity: 93.75 Kw; 330 GPH at 1 foot; sump intake – see **DSW-PU20**
- Electrical: 240 Volt, 50 Hz
- Heater: 1000 Watt industrial Heater –see **DSW-1403**
- Capacity: Holds 450Kg Load
- Filtration: Microbe impregnated 50 micron filters changeable and disposable without special tools or equipment. – see **DSW-FL4-3PK**
- Cleaning Solution: OzzyJuice – see **DSW-SW3** and **MSDS SW3**  
Aqueous based surfactant cleaner.  
NO Flashpoint  
PH Neutral biodegradable  
Non-Toxic, no caustic, non flammable, non hazardous  
NO VOC's, Phosphates, formaldehyde, bio solvents or solvents.
- Microbe Treatment: Ozzy Booster - see **DSW-1070**  
Environmental- shock resistant;  
Preserved for minimum 18 months shelf life.  
Natural occurring, non- pathogenic microbes

### 6.0 Uses

- Suitable for Car/Truck dealer workshops, Panel Beaters, Bus repairers, Mining Companies, Aviation, Defence, Councils, TAFE,

### 7.0 Documentation

- Bar Code Number: **9346080002567**
- Product Specification Manual - PS 256
- Work Instruction Manual - WI 256
- Product Costing Manual - PC 256

REV: NIL

*Kevin Pitt*

PS: 256

DATE: 10/12/13

AUTHORISED BY

PAGE: 3 of 3