



# BJT-4000V2 RHINO

MOBILE JUMP STARTER

12/24 Volt



| Model      | Voltage           | Cold Cranking Amps | Peak Amps           | Size / Weight                             |
|------------|-------------------|--------------------|---------------------|-------------------------------------------|
| BJT-4000V2 | 12 Volt / 24 Volt | CCA 900 / CCA 450  | PA 7,600 / PA 3,800 | 280 x 260 x 360 mm<br>Approximately 25 Kg |

## Model

|             |                                           |
|-------------|-------------------------------------------|
| Model       | BJT-4000V2                                |
| Description | 12 Volt and 24 Volt Portable Jump Starter |

## Performance At 12 Volts

### Performance At 12 Volts

Cold Cranking Amps: CCA 900  
Peak Amps: PA 7,600

### At 24 Volts

Cold Cranking Amps: CCA 450  
Peak Amps: PA 3,800

|         |                                                           |
|---------|-----------------------------------------------------------|
| Battery | 2 x 22 Ah Durst 212 HP AGM, Local stock, user serviceable |
| Charger | Automatic Smart Charger BCS-A 1206 12 Volts 6 Amps        |

## Features

- Complies with WHS Regulations
- Powder Coated Steel Cabinet
- Reverse Polarity Protection Buzzer - LED Warning Light
- Anti Spike Protection, Local stock, user serviceable
- Battery Isolation Switch - 12Volt - Off - 24 Volt  
Local stock, user serviceable
- Voltage Selection and Indicator Light
- Will Jump start vehicles - with dead flat Batteries
- Digital Voltmeter to monitor Voltage status with colours
- Long Life - and maintenance free
- Fuse: Ignition Protected Auto Reset - in case of short circuit  
Maintenance Free, no replacement required.
- Auto-activated Fuse installation
- Aircraft Models for various Voltages
- Custom Modifications available on request



## Physical and Dimensional Properties

|                                                                                           |
|-------------------------------------------------------------------------------------------|
| Each unit weighs approximately 25 Kg                                                      |
| Width 280 mm                                                                              |
| Length 260 mm                                                                             |
| Height 360 mm                                                                             |
| Cable Length 1.5 m                                                                        |
| Cable Size 50 mm <sup>2</sup> (AWG2/0) Superflex, dual insulated pure multi-strand copper |
| Anderson to Clamp (Standard), Anderson to Anderson and Anderson to CAT (Optional extras)  |
| Clamps: 1000A Insulated Extra heavy duty, nickel plated copper                            |

## Functions

- Multifunction Digital Volt Meter
- Warning Buzzer
- Computer Safe
- Optional trolley available
- DC Charger: Optional
- AC Charger: Automatic, Durst BCS-A1206

### Serviceability

User serviceable, does not void warranty

## Uses

- Portable high-capacity mobile jump starter.
- Suitable for Car/Light Commercial vehicle dealer workshops, Panel Beaters, Minibus repairers, Mining Companies, Aviation, Defence, Councils, TAFE, Hire Companies, Auction Yards.

## Documentation

- Bar Code Number: 934608000341
- Product Specification Manual - PS 02
- Work Instruction Manual-WI 02
- Product Costing Manual-PC 02

### Durst Industries (Aust.) Pty Ltd.

1/11 Packard Ave. Castle Hill NSW 2154 Australia  
DURST.COM.AU | SALES@DURST.COM.AU | INTL +61 2 9660 1755