

BJT-200V2 DATA SHEET



High-Performance Mobile Jump Starter

12Volt and 24 Volt





Durst Industries (Aust.) Pty Ltd. 1/11 Packard Ave. Castle Hill NSW 2154 Australia DURST.COM.AU
SALES@DURST.COM.AU
INTL +61 2 9660 1755



FEATURES

- > 12V/24V Switchable Operation: Easily switch between 12V and 24V modes for versatile use.
- > **Reverse Polarity Warning Buzzer:** Audible alert for incorrect connections, ensuring safety.
- > Anti Spike Protection: Protects sensitive vehicle electronics from voltage spikes.
- > **Auto Reset Fuse:** Automatically resets in case of a short circuit, reducing downtime.
- > Extended Life Operation: Designed for long-lasting, maintenancefree performance.
- > **Powder Coated Steel Enclosure:** Durable and weather-resistant finish for harsh conditions.
- > Quality Durable Build: All components are serviceable for extended product life.
- > Wheeled Trolley: Easy to transport across workshops or job sites.
- > High Performance Operation:
 - > 12V: 1600 Cold Cranking Amps (CCA)
 - > 24V: 800 Cold Cranking Amps (CCA)
- > Extended Cranking Time: Reliable and powerful performance for hard-to-start engines.
- > New V2 Model: Improved safety features and enhanced build quality.

PHYSICAL AND DIMENSIONAL PROPERTIES

- > Weight: Approximately 57 kg
- > Dimensions:
 - > Width: 570 mm
 - > Length: 330 mm
 - **> Height:** 620 mm
- > Cable Length: 2.0 m
- > Cable Size: Primary 70mm² (LS-704-AP350RD)



PERFORMANCE:

- > At 12 Volts:
 - > Cranking Amps (CA): 1960
 - > Cold Cranking Amps (CCA): 1600
 - > Peak Amps (est.): 7000
- > At 24 Volts:
 - > Cranking Amps (CA): 980
 - > Cold Cranking Amps (CCA): 800
 - > Peak Amps (est.): 3500
- > Charger: Automatic SmartCharger BCS-A1210, 24 Volts, 12 Amps

APPLICATIONS:

 Ideal for use in car and truck dealerships, panel beaters, bus repair workshops, mining companies, aviation and defence sectors, councils, TAFEs, hire companies, and auction yards.

DOCUMENTATION:

> Bar Code Number: 934608000358